

RESOLUTION NO. 2026 – 51

TO AWARD BID FOR A LARGE LOWBOY EQUIPMENT TRAILER TO EQUIPMENT LOGISTICS, INC.

WHEREAS, bids (CB2026-03) were received on December 11, 2025, at 2:00 p.m. for a large lowboy equipment trailer for the Street Department; and

WHEREAS, the following bids were opened:

Better Built Trailers, Inc.	Double Springs, AL	No Bid
Cowin Equipment Company	Birmingham, AL	No Bid
Econoline Trailers, Inc.	Double Springs, AL	No Bid
Equipment Logistics, Inc.	Hanceville, AL	\$112,975.22
Lone Wolf Trailer Company	Falkville, AL	No Bid

WHEREAS, the recommendation is to award the bid to Equipment Logistics, the lowest responsible bidder; and

BE IT RESOLVED by the Cullman City Council that the bid for a large lowboy equipment trailer be awarded to Equipment Logistics, Inc., the lowest responsible bidder in the total amount of \$112,975.22.

ADOPTED BY THE CITY COUNCIL this the 15th day of December 2025.

President of the City Council

ATTEST:

City Clerk

APPROVED BY THE MAYOR this the 15th day of December 2025.

Mayor

CITY OF CULLMAN	
BID TAB SHEET	
Bid Number:	CB2026-03
Date:	12.11.2025
Time:	2:00pm
FIFTH WHEEL GOOSE NECK TRAILER	

Total Bid Price

1)	Better Built Trailer	No Bid
2)	Cowin	No Bid
3)	Econoline Trailers	No Bid
4)	Equipment Logistics	\$112,975.22
5)	Lone Wolf Trailer	No Bid



Quote Date: 12-3-2025
 Quote Expires: 2026
 Quote Number: 123456
 Quote Reference: Scott Liddell

BID NO. CB2026-03
CULLMAN ALABAMA STREET DEPARTMENT
 2026 / 2027 MODEL PRICING

Workhorse 55 PVR (Model: WORKHORSE 55 PVR)	
	Est. Wt.: 23,748# +/- 3%
TRAILER - GENERAL	
Capacity: 50 tons in 12-foot length or 55 tons in 16-foot with 4 axles close coupled - GAWR and tire ratings determine legal payloads	
Length (Trailer Only): 53 feet 0 inches	
Width: 8 feet 6 inches	
Compatibility: Designed to Accept Optional 51/60 Rear Axle	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 7in overall gooseneck length) set up for wetline operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Kingpin: Kingpin at 102 inch radius	
Power Source: 13 HP HONDA POWER UNIT / SELF CONTAINED WITH ALUMINUM TOP PROTECTION PLATE	INCLUDED
Tool Box: Open storage area located in back of gooseneck with chain bar	
Hydraulic Fittings: OEM Standard 1/2 inch	
DECK	
Framework: All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs	
Deck Design: Flat level deck design (tapered beam design)	
Deck Length: 24 feet 0 inches Clear Deck Length	
Loaded Deck Height: 22 inches with 6 inches Ground Clearance	
Crossmembers: On 22 inch Centers (Nominal)	
Flooring: 1.5 inch nominal apitong wood (full width)	
Front Ramps: Apitong Wood Filled Double Hinged Adjustable Width to 44 inches Inside to inside (9 degree load angle)	
Extension Brackets: 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type	INCLUDED
Tool Box: Preforated plate under hammer plate forming one storage area (Storage area not accessible when covered rear bogie is in place)	
Hammer Plate: Hammer Plate installed over recessed crossmembers. Preforated plate under hammer plate forming one storage area; includes 1 pair of D rings (Hammer Plate not accessible when covered rear bogie is in place)	
REAR BRIDGE	
Front Bogie Ramp: Sloped (16 degree angle)	
Boom Trough: Low Boom Well, with V crossmember with bolt-in V pan	
Deck to Bogie Connection: Fixed w/ ramps outboard mainbeams, apitong wood filled	
Bolsters: Recessed	
Covered Rear Bogie: Load Bearing Wheel Covers- Apitong Wood Filled with center insert for full width loading (insert has 2-point lift capability; bolts in	
Rear Bogie Height: 43 inches	
Connections for Future Axle Attachment: Air and Electrical Connections to Go Along with Connecting Ears	
Accent Package: None	

AXLES	
Number of Axles: 3	
Axle Capacity: 22,500 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (Between Axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount	
Spring Brakes: Spring brakes on axle 2	
Dust Shields: None	
Hubodometer: None	
SUSPENSION	
Suspension: Air Ride	
ABS: None	
Third Lift Axle: Air Lift Installed on Third Axle	
Chain Lift: First Axle (acts as a limit chains)	
Override Chains: Override Chains Axle 2 & 3	
Ride Height Control: 7-position mechanical ride height control system	
Dump Valve: Automatic/Manual Raise/Lower Control	
Liquid Filled Gauge: None	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 Lvl One Buffed Outside/Steel Inside - Hub-Piloted	INCLUDED
Tires: 255/70R 22.5 H Ply OEM Standard	
Tire Inflation System: None	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
Tail Lights: 3 Tail Light Package	
Marker Lights: 3 Marker Lights Per Side Including Mid-Turn	
Electrical Receptacle: J560 7-Pin Connector	
Additional Marker Lights: - 14 EXTRA MARKER LIGHTS	INCLUDED
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 17 Pair - 34 Total	
Flag Holders: 2 Pair Flag Holders	
VIN Plate: Bilingual VIN Plate	
Registration/Document Holder: Registration/document holder installed	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	
AVAILABLE COMPONENTS	
Flip Axle: None	
Dust Shields on Flip Axle: None	
Additional Options:	
TRAILER IS SET UP TO TAKE A 4TH PIN ON AXLE	
CHAIN SLOTS INCLUDED DOWN BOTH SIDES OF DECK	INCLUDED
TWILIGHT PACKAGE	INCLUDED
NET	\$112,550.22
FET IS NOT INCLUDED	
FET TIRE CREDIT	
FREIGHT	\$400.00
TITLE APP	\$25
TOTAL	\$112,975.22
Total Weight	Est. Wt.: 23,748# +/- 3%


EQUIPMENT LOGISTICS

ATTN - SCOTT LIDDELL PH-205-999-7776

* 210 CAMPBELL DR HANCEVILLE, AL 35077*

SCOTT@BUYATRILER.COM

SIGNATURE



DATE 12-3-25

TRAILER IS IN STOCK.

**CITY OF CULLMAN
INVITATION TO BID
BID NO. CB2026-03**

December 2, 2025

You are invited to bid on the following item subject to the terms and conditions set forth.

SEALED BID: Submitted bids must be sealed in an envelope with Bid No. CB2026-03 clearly marked on the outside of the envelope to be considered.

Sealed bids must be received at Cullman City Hall by no later than 2:00 p.m. on THURSDAY, DECEMBER 9, 2025.

Sealed bids will be opened at 2:00 p.m. on THURSDAY, DECEMBER 9, 2025.

**Bids may be received by hand, delivered to Cullman City Hall, 204 2nd Ave NE, Cullman, AL 35055
OR by mail to City of Cullman, PO Box 278, Cullman, AL 35056-0278.**

The City of Cullman reserves the right to reject any and all bids without cause.

The low bidder will be required to purchase a proper City business license and/or permits as required by City ordinances.

Must be available for immediate delivery. Delivery point: Cullman, Alabama.

This is not an order.

One or More 2026 / 2027 Model Fifth Wheel Gooseneck Trailer	Est. Wt.: 23,748# +/- 3%
TRAILER - GENERAL	
Capacity: 50 tons in 12-foot length or 55 tons in 16-foot with 4 axles close coupled - GAWR and tire ratings determine legal payloads	
Length (Trailer Only): 53 feet 0 inches	
Width: 8 feet 6 inches	
Compatibility: Designed to Accept Optional 51/60 Rear Axle	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 7in overall gooseneck length) set up for wetline operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Kingpin: Kingpin at 102 inch radius	
Power Source: 13 HP POWER UNIT / SELF CONTAINED WITH ALUMINUM TOP PROTECTION PLATE	INCLUDED
Tool Box: Open storage area located in back of gooseneck with chain bar	
Hydraulic Fittings: OEM Standard 1/2 inch	
DECK	
Framework: All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs	
Deck Design: Flat level deck design (tapered beam design)	
Deck Length: 24 feet 0 inches Clear Deck Length	
Loaded Deck Height: 22 inches with 6 inches Ground Clearance	
Crossmembers: On 22 inch Centers (Nominal)	
Flooring: 1.5 inch nominal apitong wood (full width)	
Front Ramps: Apitong Wood Filled Double Hinged Adjustable Width to 44 inches inside to inside (9 degree load angle)	
Extension Brackets: 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type	INCLUDED
Tool Box: Perforated plate under hammer plate forming one storage area (Storage area not accessible when covered rear bogie is in place)	
Hammer Plate: Hammer Plate installed over recessed crossmembers. Perforated plate under hammer plate forming one storage area; includes 1 pair of D rings (Hammer Plate not accessible when covered rear bogie is in place)	
REAR BRIDGE	
Front Bogie Ramp: Sloped (16 degree angle)	
Boom Trough: Low Boom Well, with V crossmember with bolt-in V pan	
Deck to Bogie Connection: Fixed w/ ramps outboard mainbeams, apitong wood filled	
Bolsters: Recessed	
Covered Rear Bogie: Load Bearing Wheel Covers- Apitong Wood Filled with center insert for full width loading (insert has 2-point lift capability; bolts in	
Rear Bogie Height: 43 inches	
Connections for Future Axle Attachment: Air and Electrical Connections to Go Along with Connecting Ears	
Accent Package: None	
AXLES	
Number of Axles: 3	
Axle Capacity: 22,500 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (Between Axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount	

Spring Brakes: Spring brakes on axle 2	
Dust Shields: None	
Hubodometer: None	
SUSPENSION	
Suspension: Air Ride	
ABS: None	
Third Lift Axle: Air Lift Installed on Third Axle	
Chain Lift: First Axle (acts as a limit chains)	
Override Chains: Override Chains Axle 2 & 3	
Ride Height Control: 7-position mechanical ride height control system	
Dump Valve: Automatic/Manual Raise/Lower Control	
Liquid Filled Gauge: None	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 Lvl One Buffed Outside/Steel Inside - Hub-Piloted	INCLUDED
Tires: 255/70R 22.5 H Ply OEM Standard	
Tire Inflation System: None	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
Tail Lights: 3 Tail Light Package	
Marker Lights: 3 Marker Lights Per Side Including Mid-Turn	
Electrical Receptacle: J560 7-Pin Connector	
Additional Marker Lights: - 14 EXTRA MARKER LIGHTS	INCLUDED
PAINT	
Paint: black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 17 Pair - 34 Total	
Flag Holders: 2 Pair Flag Holders	
VIN Plate: Bilingual VIN Plate	
Registration/Document Holder: Registration/document holder installed	
Please Note: Price includes commodity surcharges	
Commercial Terms:	
AVAILABLE COMPONENTS	
Flip Axle: None	
Dust Shields on Flip Axle: None	
Additional Options:	
TRAILER IS SET UP TO TAKE A 4 TH PIN ON AXLE	
CHAIN SLOTS INCLUDED DOWN BOTH SIDES OF DECK	INCLUDED
TWILIGHT PACKAGE	INCLUDED
TOTAL BID	\$ 112,975.22

BIDDER CERTIFICATION: It is hereby affirmed that the above bid has been made in accordance with the terms and conditions set forth and that the Bidder will accept any awards made to him as a result of this quotation.

SEALED BID: Submitted bids must be sealed in an envelope with Bid No. CB2020-03 clearly marked on the outside of the envelope to be considered.

Sealed bids must be received at Cullman City Hall by no later than 2:00 p.m. or THURSDAY, DECEMBER 9, 2025.

Sealed bids will be opened at 2:00 p.m. on THURSDAY, DECEMBER 9, 2025.

Bids may be received by hand, delivered to Cullman City Hall, 204 2nd Ave NE, Cullman, AL 35055
OR by mail to City of Cullman, PO Box 278, Cullman, AL 35056-0278.

BIDDER INFORMATION

Date: 12-3-25	Contact Name: SCOTT LIDDELL
Company: EQUIPMENT LOGISTICS	Contact Phone: 205-999-7726
Address: 210 CAMPBELL DR	Contact Email: SCOTT@BUYATRAILER.COM
City, State, Zip: CULLMAN, AL 35077	Signature: Scott Liddell

For questions regarding this bid, please contact Deputy City Clerk Pam Leslie either by phone at 256-775-7104 or by email at cityclerk@cullmanal.gov.